

General Information

RIMS FOR '50' SERIES - METRIC DESIGNATION

TYRE SIZE			APPROVED RIMS							
165/50	R	15	41/2J	5J	51/2J	6J				
175/50	R	13	5.00B	5J	5.50B	51/2J	6.00B	6J		
	R	14, 15, 16	5J	51/2J	6J					
185/50	R	13	5.00B	5J	5.50B	51/2J	6.00B	6J		61/2J
	R	14, 16	5J	51/2J	6J	61/2J				
195/50	R	13	5.50B	51/2J	6.00B	6J	61/2J	7J		
	R	15, 16	51/2J	6J	61/2J	7J				
205/50	R	13	5.50B	51/2J	6.00B	6J	61/2J	7J		71/2J
	R	14, 15, 16, 17	51/2J	6J	61/2J	7J	71/2J			
215/50	R	13	6.00B	6J	61/2J	7J	71/2J			
	R	15, 16, 17, 18	6J	61/2J	7J	71/2J				
225/50	R	15, 16, 17	6J	61/2J	7J	71/2J	8J			
235/50	R	16, 17, 18	61/2J	7J	71/2J	8J	81/2J			
245/50	R	15, 16, 17, 18, 19	7J	71/2J	8J	81/2J				
255/50	R	16, 17, 18, 19, 20	7J	71/2J	8J	81/2J	9J			
265/50	R	16, 20	71/2J	8J	81/2J	9J	91/2J			
275/50	R	17, 18, 19, 20	71/2J	8J	81/2J	9J	91/2J			
285/50	R	15, 18, 20	8J	81/2J	9J	91/2J	10J			
295/50	R	15, 16, 20	8J	81/2J	9J	91/2J	10J	101/2J		
305/50	R	15	81/2J	9J	91/2J	10J	101/2J	11J		
315/50	R	22	81/2J	9J	91/2J	10J	101/2J	11J		
325/50	R	20	9J	91/2J	10J	101/2J	11J	111/2J		

RIMS FOR '45' SERIES - METRIC DESIGNATION

TYRE SIZE			APPROVED RIMS			
165/45	R	15	5J	51/2J	6J	
175/45	R	15	51/2J	6J	61/2J	
185/45	R	15	6J	61/2J	7J	
195/45	R	13, 14, 15, 16, 17	6J	61/2J	7J	71/2J
205/45	R	14, 15, 16, 17, 18	61/2J	7J	71/2J	
215/45	R	15, 16, 17, 18	7J	71/2J	8J	
225/45	R	13, 16, 17, 18, 19	7J	71/2J	8J	81/2J
235/45	R	15, 17, 18, 19	71/2J	8J	81/2J	9J
245/45	R	13, 16, 17, 18, 19	71/2J	8J	81/2J	9J
255/45	R	15, 17, 18, 19	8J	81/2J	9J	91/2J
265/45	R	20	81/2J	9J	91/2J	10J 101/2J
275/45	R13, 17, 18, 19, 20, 22		81/2J	9J	91/2J	10J 101/2J
285/45	R	18, 19, 20, 21	9J	91/2J	10J	101/2J
295/45	R	18, 19, 20	91/2J	10J	101/2J	11J
305/45	R	20, 22	91/2J	10J	101/2J	11J 111/2J

RIMS FOR '40' SERIES - METRIC DESIGNATION

TYRE SIZE			APPROVED RIMS			
195/40	R	14, 16, 17	61/2J	7J	71/2J	
205/40	R	13, 16, 17, 18	7J	71/2J	8J	
215/40	R	14, 15, 16, 17, 18	7J	71/2J	8J	81/2J
225/40	R	14, 16, 17, 18, 19	71/2J	8J	81/2J	9J
235/40	R	17, 18, 19	8J	81/2J	9J	91/2J
245/40	R	17, 18, 19, 20	8J	81/2J	9J	91/2J
255/40	R	16, 17, 18, 19	81/2J	9J	91/2J	10J
265/40	R	17, 18	9J	91/2J	10J	101/2J
275/40	R	17, 18, 19, 20	9J	91/2J	10J	101/2J 11J
285/40	R	15, 17, 18, 19, 20	91/2J	10J	101/2J	11J
295/40	R	17, 18, 20, 22, 24	10J	101/2J	11J	111/2J
305/40	R	22, 23	10J	101/2J	11J	111/2J 12J
315/40	R	23	101/2J	11J	111/2J	12J 121/2J
325/40	R	22	11J	111/2J	12J	121/2J 13J

General Information

RIMS FOR '35' SERIES - METRIC DESIGNATION

TYRE SIZE		APPROVED RIMS			
215/35	R 16, 17, 18, 19	7J	71/2J	8J	81/2J
225/35	R 17, 18, 19	71/2J	8J	81/2J	9J
235/35	R 15, 18, 19	8J	81/2J	9J	91/2J
245/35	R15, 16, 17, 18, 19, 20, 21	8J	81/2J	9J	91/2J
255/35	R14, 16, 18, 19, 20, 21	81/2J	9J	91/2J	10J
265/35	R 17, 18, 19, 20, 22	9J	91/2J	10J	101/2J
275/35	R 17, 18, 19, 20, 22	9J	91/2J	10J	101/2J 11J
285/35	R 18, 19, 21, 22	91/2J	10J	101/2J	11J
295/35	R 18, 19, 24	10J	101/2J	11J	111/2J
305/35	R 23, 24	10J	101/2J	11J	111/2J 12J
315/35	R 17, 20, 24	101/2J	11J	111/2J	12J 121/2J
335/35	R 17	11J	111/2J	12J	121/2J 13J
345/35	R 15, 18, 19	111/2J	12J	121/2J	13J 131/2J

RIMS FOR '30' SERIES - METRIC DESIGNATION

TYRE SIZE		APPROVED RIMS			
225/30	R 18, 19, 20	8J			
245/30	R 19, 20	8J	81/2J	9J	
255/30	R 18, 19, 20, 21, 22	81/2J	9J	91/2J	
265/30	R 18, 19, 20, 22	9J	91/2J	10J	
275/30	R 19, 20, 23	9J	91/2J	10J	
285/30	R 18, 19, 20, 21, 22	91/2J	10J	101/2J	
295/30	R 18, 19, 21, 22	10J	101/2J	11J	
305/30	R 19	101/2J	11J	111/2J	
315/30	R 18, 22, 24	101/2J	11J	111/2J	
325/30	R 18, 17, 21	11J	111/2J	12J	
335/30	R 18, 20	111/2J	12J	121/2J	
345/30	R 19	111/2J	12J	121/2J	

RIMS FOR '25' SERIES - METRIC DESIGNATION

TYRE SIZE		APPROVED RIMS			
275/25	R 20	10J			
285/25	R 20	101/2J			
295/25	R 20, 21, 22	10J	101/2J	11J	
305/25	R 19, 20, 23	101/2J	11J	111/2J	
315/25	R 19, 23	11J	111/2J	12J	
325/25	R 20	111/2J	12J	121/2J	
335/25	R 19	111/2J	12J	121/2J	
345/25	R 20	12J	121/2J	13J	
355/25	R 19	121/2J	13J	131/2J	

The Measuring rim widths are shown in bold.

- **CONSULT THE TYRE MANUFACTURER WITH REGARD TO** : the use of B flange rims with tyres for which B flange rims are not specified above.
- **CONSULT THE TYRE AND RIM/WHEEL MANUFACTURERS** for confirmation of the suitability of the tyre/wheel assembly to the intended service.

LEGEND:



Series Pattern Spec Tyre Size Load Index Speed Symbol Measuring Rim Overall Diameter Overall Width Static Loaded Radius Rolling Circumference