



300V Power 5W-40

Racing lubricant for racing cars

100% Synthetic – Double Ester Technology

TYPE OF USE

Racing cars with atmospheric or turbocharged engines, race engines operating in a wide range of rpm and temperatures : race on tracks, single brand races, rallyes, uphill races...
Engine producing medium fuel dilution in the oil.

Other applications : Gasoline or diesel engines, turbocharged, direct injection and catalytic converters.

PERFORMANCES

STANDARDS Above existing standards.
Reference team SUBARU WRT, World Rally championship –
Graff Racing, Formula Renault (open wheel cars, single brand race)

Double Ester technology : maximum oil film resistance, balanced polarity, resistance at very high temperature.

Friction Modifier : maximum power output, decrease operating temperature.

0% shear loss : Stable oil pressure whatever using conditions.

Maximum anti-wear resistance.

Perfect engine cleanliness.

5W-40 grade allows excellent oil flow into the engine, fastest oil pressure set up, faster rev raisings and at the same time high oil pressure at high rpm and high temperatures.

RECOMMENDATIONS

Oil change : according to your own use.
Can be mixed with synthetic or mineral lubricants.

PROPERTIES

Viscosity grade	SAE J 300	5W-40
Density at 15°C (59°F)	ASTM D1298	0.905
Viscosity at 100°C (212°F)	ASTM D445	13.8 mm ² /s
Viscosity at 40°C (104°F)	ASTM D445	80.8 mm ² /s
Viscosity Index	ASTM D2270	176
HTHS viscosity at 150°C (302°F)	ASTM D4741	4.51 mPa.s
Pour point	ASTM D97	-36°C / -33°F
Flash point	ASTM D92	216°C / 420°F
TBN	ASTM D 2896	10.9 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France

MOTUL . 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel 33 1 48 11 70 00 - FAX 33 1 48 33 28 79 . Site Web : www.motul.fr

8256

12/03