



TAF-X

Synthetic Automotive Gear Oil

DESCRIPTION

Castrol TAF-X is a fully synthetic SAE 75W-90 multigrade gear oil. It is formulated with specially selected additives to combine extreme pressure qualities with synchro-cone compatibility.

APPLICATION

It is designed to help improve cold weather gear selection and keep transmission noise levels to a minimum at high operating temperatures.

Castrol TAF-X is recommended for use in manual gearboxes, transaxles, transfer boxes and final drives where an API GL4 lubricant is specified.

TYPICAL PHYSICAL CHARACTERISTICS

API Service Level	GL4
SAE Viscosity Rating	75W/90
Density @ 20°C	0.860
Viscosity @ 40°C, cSt	73
Viscosity @ 4100°C, cSt	14.4
Viscosity Index	210
Flash Point, °C	220
Pour Point, °C	-45

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.
Castrol (UK) Ltd. or its subsidiaries will not accept liability if the product is used other than in the manner or with the precautions or for the purpose/s specified. Before the product is used other than as directed, advice should be obtained from the local Castrol office.

Typical Characteristics

Test Methods	Units	Value:
--------------	-------	--------

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Data sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

Castrol UK Ltd, Wakefield House, Pipers Way, SWINDON, Wiltshire. SN3 1RE www.castrol.com/uk
Telephone: 01793 512712
Automotive Technical Helpline: 01793 452222
Orders/Enquiries: 0845 6008125 (Workshop Customer Order Line) 0845 6008131 (Retail Customer Order Line)

Castrol Ireland Ltd, Wakefield House, Pipers Way, SWINDON, Wiltshire. SN3 1RE www.castrol.com/ie
Automotive Technical Helpline: 1800 509 353
Orders/Enquiries: 1850 930 394

Date Created: 10/10/2002 17:39:29 Last Modified:14/11/2008